

## SMART PROJECTOR PAINTS

### APPLICATION GUIDE

This application guide contains the steps for all Smarter Surfaces projector paint products. These include:

- SMART PROJECTOR PAINT PRO
- SMART PROJECTOR PAINT
- SMART PROJECTOR PAINT CONTRAST

All Projector Paint products are suitable for use on plaster, wallboards, wood, metal and concrete. For interior use only. Each kit covers an area of 6m<sup>2</sup> / 65 sq. ft. This will create up to the following screen sizes:

- 4:3 - max dimensions of 2.8m X 2.1m (9.18ft x 6.88ft)
- 2.35:1 - max dimensions of 3.71m X 1.58m (12.71ft x 5.18ft)
- 16:9 - max dimensions of 3.25m X 1.83m (10.66ft x 6ft)
- 2.40:1 - max dimensions of 3.79m X 1.58m (12.43ft x 5.18ft)

Please read the section that is relevant to your application of your product.

## HOW TO APPLY SMART PROJECTOR PAINT AND SMART PROJECTOR PAINT PRO

Smart Projector Paints are extremely high quality projection paints that enable users to project the clearest images possible. Smart Projector Paint and Smart Projector Paint Pro come in a white finish and are designed to be used with standard, interactive, 3D, and 4K front projectors. (See below for Smart Projector Paint Contrast.)

### 1

#### PREPARE THE SURFACE

- All surfaces to be painted should be clean, dry and free from loose materials.
- Measure the area you wish to paint and clearly mark it using masking tape.
- **Smart Projector Paint:** Prime bare, untreated surfaces with Smart White Primer.
- **Smart Projector Paint Pro:** we recommend always applying Smart White Primer (included in your kit) before the paint for best results.
- Once primed, lightly sand the surface.

### 2

#### APPLY THE PROJECTOR PAINT

- Stir paint thoroughly before use.
- For best results, apply paint using a mohair or lint free short pile roller sleeve.
- Apply 2 coats allowing the first coat to dry before applying the second coat (approx. 2-4 hours at 20°).

### 3

#### DRYING TIME

- Smart Projector Paint will be touch-dry in 1 hour and usable after 24 hours.

## HOW TO APPLY SMART PROJECTOR PAINT CONTRAST

Smart Projector Paint Contrast is applied in two coats (a base coat, then a top coat) and comes in a gray finish. This product is designed to be used with all interactive, HD and standard projectors, and works particularly well with 4K projectors in low ambient light.

### 1

#### PREPARE THE SURFACE

- All surfaces to be painted should be clean, dry and free from loose materials.
- Measure the area you wish to paint and clearly mark it using masking tape.
- Prime bare, untreated surfaces with **Smart White Primer**.
- Once primed, lightly sand the surface.

### 2

#### APPLY THE BASECOAT OF PROJECTOR PAINT

- Stir paint thoroughly before use. If applying your paint to new plaster work apply one coat of standard white paint or primer then fill and sand smooth any defects.

##### Base Coat

- Apply your first coat of the base coat tin using a mohair or lint free short pile roller sleeve.
- Sand smooth when dry and then add the second coat.
- Wait for paint to fully dry before adding the Smart Projector Paint Contrast top coat (approx. 2-4 hours at 20°).

##### Top Coat

- Ensure the base coat is smooth and free from surface defects.
- Apply the first coat with a mohair or lint free short pile roller sleeve. Allow to dry before applying the second coat.

### 3

#### DRYING TIME

- Once all coats are applied Smart Projector Paint Contrast will be ready to use in 24 hours.

### PRODUCT LIABILITY CLAUSE

The sale of our products is subject to our General Terms and Conditions available on [www.smartersurfaces.com](http://www.smartersurfaces.com)

### SUPPORT



EMAIL:  
[support@smartersurfaces.com](mailto:support@smartersurfaces.com)



PHONE (IRE):  
+353 1 412 6200



WEBSITE:  
[www.smartersurfaces.com](http://www.smartersurfaces.com)